

OIL S&D HOSE 150 PSI W.P.

Lining

Black, oil and fuel resistant nitrile rubber.

Reinforcement

Synthetic textile. Steel wire helix embedded between the layers.

Cover

Black, abrasion, ozone, weather, heat and oil resistant neoprene rubber

Aromatics

Resistant to maximum 50% aromatic content

Temperature

Suitable for use in the range -31°F to +212°F

Coil Lengths

Available in 20' and 100' lengths

CODE	DIMENSION		WORKING PRESSURE MAX PSI	BURSTING PRESSURE MAX PSI	WEIGHT LB/100	BENDING RADIUS MIN. (IN)	LENGTHS FT.
	I.D. INCH	O.D. INCH					
WHS-OSD75	3/4"	1.14"	150	450	40	3	100
WHS-OSD10	1"	1.42"	150	450	50	4	100
WHS-OSD15	1-1/2"	1.93"	150	450	69	6	100
WHS-OSD20	2"	2.50"	150	450	89	8	100
WHS-OSD25	2-1/2"	2.95"	150	450	140	10	100
WHS-OSD30	3"	3.62"	150	450	167	12	20, 100
WHS-OSD40	4"	4.57"	150	450	228	16	20, 100
WHS-OSD60	6"	6.85"	150	450	481	24	20

Inner and outer material, number of reinforcement, reinforcement material may change, if hose construction meets customer requirements.